Amendments to the Claims

| 1. (Currently Amended) A composite substrate comprising |
|--------------------------------------------------------------------------------------------|
| a carrier composed of a carrier material, |
| a first layer composed of a first material, and |
| an intermediate layer composed of a second material being located between the |
| carrier and the first layer, wherein the first material has a dilatation behavior being |
| substantially the same as that of the carrier material, and having a dilatation mismatch |
| with the second material, the intermediate layer having structures of second material for |
| absorbing stress originating from the dilatation mismatch. |
| 2. (Original) A composite substrate according to claim 1, wherein the intermediate layer |
| |
| has a thickness, and the structures extend through the thickness of the intermediate layer |
| 3. (Original) A composite substrate according to claim 1, wherein the structures further |
| extend into the carrier. |
| 4 (Quinium) A commonite substante according to alaim 1 subspain the comics meetorial is |
| 4. (Original) A composite substrate according to claim 1, wherein the carrier material is |
| the same as the first material. |
| 5. (Currently Amended) A composite substrate according to any of the previous claims, |
| according to claim 1, wherein the carrier material and the first material are |
| semiconductors. |
| 6 (Commenter Amondae) A commenter as between a coordinate any of the massicus alaims |
| 6. (Currently Amended) A composite substrate according to any of the previous claims, |
| according to claim 1, wherein the second material is an electrically insulating material. |
| |

7. (Currently Amended) A composite substrate according to any of the previous claims,

according to claim 1, the intermediate layer lying in a plane, wherein the dimensions of

the structures in the plane of the intermediate layer are less than a centimeter.

Appl. No. Unassigned; Docket No. NL 021443 US Amdt. dated May 31, 2005 Preliminary Amendment

- 8. (Currently Amended) A composite substrate according to any of the previous claims, according to claim 1, wherein the carrier lies in a plane and wherein the structures have a line-symmetric shape in a cross-section perpendicular to the plane of the carrier.
- 9. (Currently Amended) A composite substrate according to any of the previous claims, according to claim 1, wherein the carrier lies in a plane and wherein the structures have a circular, square, rectangular or rhombic shape in a cross-section parallel to the plane of the carrier.
- 10. (Currently Amended) A composite substrate according to any of the previous claims, according to claim 1, wherein the composite substrate is a silicon-on-insulator wafer.
- 11. (Original) A method to relieve stress in a composite substrate, comprising:

 providing a carrier, composed of a carrier material, with on top thereof an intermediate layer of a second material,

forming in the intermediate layer structures which extend through the intermediate layer,

bonding on the intermediate layer a first substrate of a first material having a dilatation behavior being substantially the same as that of the carrier material.

- 12. (Original) A method according to claim 11, in which the structures are formed into the carrier.
- 13. (Currently Amended) A method according to claim 11 or 12, according to claim 11, wherein the forming of the structures is executed by integrally patterning the structures over the intermediate layer.
- 14. (Currently Amended) A method according to claim 11 or 12, according to claim 11, wherein the forming of the structures is executed by locally patterning the structures in clusters over the intermediate layer.

Appl. No. Unassigned; Docket No. NL 021443 US Amdt. dated May 31, 2005

Preliminary Amendment

15. (Currently Amended) A method according to any of claims 11 to 14, according to claim 11, wherein the patterning comprises applying millimeter, micrometer or nanometer structural texturing.

16. (Currently Amended) A method according to any of claims 11-to 14, according to claim 11, wherein the patterning comprises applying imprint lithography.

17. (Currently Amended) A method according to any of claims 11 to 16, according to claim 11, wherein the intermediate layer lies in a plane, and wherein the forming of the structures is such that the dimensions of the structures in the plane of the intermediate layer are less than a centimeter.

18. (Currently Amended) A method according to any of claims 11 to 17, according to claim 11, wherein the carrier lies in a plane, and wherein the forming of the structures is such that the structures have a line-symmetric shape in a cross-section perpendicular to the plane of the carrier.

19. (Currently Amended) A method according to any of claims 11 to 18, according to claim 11, wherein the carrier lies in a plane, and wherein the forming of the structures is such that the structures have a circular, square, rectangular or rhombic shape in a cross-section parallel to the plane of the carrier.

20. (Currently Amended) Use of the method of any of claims 11 to 19 as recited claim 11, for making a silicon-on-insulator substrate.